

GENERAL NOTES:

CONTRACTOR RESPONSIBILITY-CONTRACTOR IS SOLELY RESPONSIBLE FOR:

- . VIEWING SITE AND INCLUDING ANY SPECIAL CONDITIONS NECESSARY TO PERFORM THE
- WORK AS DESCRIBED IN THE DRAWINGS.

 ESTABLISHING CONTROL OF THE SITE VIA SURVEY, AND LAYOUT.
- OBTAINING AND PAYING FOR ALL PERMITS
- . UBLIAINING AND PAYING FOR ALL PERMITS.
 PAYING FOR ALL TEMPORARY UTILITIES AND FACILITIES.
 CHECKING AND CONFIRMING ALL DIMENSIONS, AND LAYOUTS.
 SCHEDULING AND SEQUENCING.
- CONSTRUCTION MEANS, METHODS AND TECHNIQUES
- MAINTAINING DRAWINGS AND PERMITS ON SITE.
 JOB SITE SAFETY
 COORDINATION BETWEEN TRADES, AND SUPPLIERS.

- 15. REPAIRING ANY WORK DAMAGED BY HIS FORCES WHILE PERFORMING THIS CONTRACT. 16. GIVING WARRANTY FOR HIS WORK FOR A PERIOD OF ONE YEAR FROM THE DATE OF FINAL

REVIEW OF WORK BY DESIGNERS-

CONTRACTOR SHALL NOTIFY ARCHITECT BEFORE PROJECT STARTS.

CONTRACTOR SHALL NOTIFY ARCHITECT, ONE WEEK PRIOR TO:

- 17. POURING CONCRETE
- 18. INSULATING 19. INSTALLING DRYWALL 20. FINAL INSPECTION

SHOP DRAWINGS-

ALL SHOP DRAWINGS SHALL BE SUBMITTED 30 DAYS AFTER CONTRACT AWARD.

GENERAL CONTRACTOR SHALL APPROVE SHOP DRAWINGS, PRIOR TO SUBMITTING TO ARCHITECT OR ENGINEER.

NON SUBMISSION DOES NOT CONSTITUTE APPROVAL OF ANY WORK.

NO EXCEPTIONS TAKEN DOES NOT RELIEVE THE CONTRACTOR OF PERFORMING ANY OTHER WORK ON THE DRAWINGS.

CONTRACTOR SHALL EXPECT A MINIMUM OF 2 WEEKS FOR DESIGNERS' REVIEW TIME

ANY VARIANCE FROM THE ORIGINAL DESIGN SHALL BE NOTED.

ANY SUBSTITUTION NOT INDICATED SHALL NOT CONSTITUTE APPROVAL OF A CHANGE

SHOP DRAWINGS ARE NOT COORDINATION DRAWINGS

DESIGNERS ARE NOT RESPONSIBLE FOR DIMENSIONS.

CONTRACTOR TO ENSURE MATERIALS AND ASSEMBLIES ARE COMPATIBLE AND ACCEPTABLE TO THE MANUFACTURER. ALL ASSEMBLY MATERIALS SHALL BE FROM A SINGLE SOURCE AS MUCH AS POSSIBLE.

REQUEST FOR INFORMATION -

ONLY RFI'S SENT THROUGH BY THE OWNER AND AWARDING CONTRACTOR WILL BE ANSWERED. SUBCONTRACTORS MUST SUBMIT RFI'S THROUGH THE GENERAL CONTRACTOR.

BIDDING PHASE - OWNER AND AWARDING CONTRACTOR ARE RESPONSIBLE FOR COMPILING AND AGGREGATING RFTS AND SUBMITTING TO THE ARCHITECT OR DESIGNER AT ONE TIME ONLY. ARCHITECT OR DESIGNER HAS ONE WEEK TO RESPOND, QUESTIONS MUST BE COMPLETE, NOT PIECEMEAL AND SHOULD BE SUBMITTED BY CSI DIVISION.

CHANGE ORDERS-

CONTRACTOR SHALL VISIT THE SITE AND BE THOROUGHLY ACQUAINTED WITH THE PROJECT PRIOR TO SUBMITTING A PRICE. ADDITIONAL MONEY WILL NOT BE GRANTED FOR WORK NOT CLARIFIED PRIOR TO BIDDING

DESIGNER SHALL BE NOTIFIED OF ANY CHANGE TO THE DRAWINGS, UNFORESEEN FIELD CONDITIONS OR DISCREPANCIES PRIOR TO PERFORMING WORK.

ANY PROPOSED CHANGES SHALL BE ACCOMPANIED WITH A WRITTEN DESCRIPTION OR A SKETCH FOR CLARIFICATION.

ALL CHANGE ORDERS SHALL BE APPROVED PRIOR TO PERFORMING WORK.

CHANGE ORDERS SHALL BE PRICED FITHER LUMP SUM OR UNIT PRICE OR TIME AND

ANY SUBSTITUTION REQUEST SHALL BE MADE VIA CHANGE ORDER, AND NOT VIA SHOP DRAWINGS UNLESS AGREED TO.

ANY CHANGE SHALL STATE THE CREDIT OR COST ADD AND/OR ANY CHANGE TO THE SCHEDULE.

REQUISITIONS-

ANY REQUISITION REQUIRED TO BE SIGNED BY THE ARCHITECT SHALL BE SUBMITTED A MINIMUM OF ONE WEEK PRIOR TO BEING SUBMITTED TO THE BANK FOR REVIEW.

CONTRACTOR SHALL PROVIDE RECEIPTS AND INSURANCE CERTIFICATES FOR ANY MATERIALS FOR PAYMENT FOR ANY UNINSTALLED MATERIALS.

STEEL NOTES:

1. ALL COLUMNS: A36, STEEL PIPE, A46 STEEL TUBE.


2. BOLTS: A325. ANCHOR BOLTS: A307


STRUCTURAL STEEL NOTES:

- . ALL STRUCTURAL STEEL SHALL CONFORM TO ASTM A50 SPECIFICATIONS, EXCEPT SQUARE STEEL TUBE COLUMNS.
- 2. ALL SQUARE STEEL TUBE COLUMNS SHALL CONFORM TO ASTM A500, WITH A MINIMUM YIELD STRESS OF 46,000 PSI.
- ALL SHOP CONNECTIONS SHALL BE WELDED.
 FIELD CONNECTION SHALL BE MADE WITH HIGH STRENGTH FRICTION BOLTS. MEETING A325-X SPECIFICATIONS
- ALL BOLTS SHALL BE 3/4" IN DIAMETER, OR AS NOTED ON DRAWINGS. HOLES SHALL BE 1/16" LARGER.
- 6. ALL STRUCTURAL STEEL SHALL RECEIVE ONE SHOP COAT OF RUST INHIBITIVE PAINT; SUCH AS TNEMEC-99, OR RUST
- INHIBITOR BY "MAINLINE" OR PAINT AS NOTED IN THE SPECIFICATIONS AFTER STRUCTURAL STEEL ERECTION IS IN PLACE, ALL EXPOSED AREAS SHALL BE TOUCHED UP. SEE SPECIFICATIONS ON PAINTING FOR ADDITIONAL
- 8. PROVIDE 3/4: GROUT, 3,000 PSI, AND 1/4" THICK LEVELING PLATES UNDER ALL
- COLUMN BASE PLATES, WITH FOUR


 (4) 3/4" DIAMETER x 16" LONG ANCHOR BOLTS; OR AS NOTED.
- 9. PROVIDE A MINIMUM OF 8" BEARING ON EACH SIDE OF LINTELS AND HEADERS OVER DOORS, WINDOWS, LOUVERS, AND OPENINGS, ETC.
- 10. THE CONTRACTOR SHALL SUBMIT A REPRODUCIBLE SEPIA AND FOUR PRINTS OF SHOP DRAWINGS: SHOWING ALL STRUCTURAL STEEL SIZES, CONNECTIONS AND DETAILS, TO THE ARCHITECT
- FOR HIS APPROVAL. FABRICATION
- OF STRUCTURAL STEEL MEMBERS SHALL NOT BEGIN WITHOUT PRIOR WRITTEN APPROVAL BY THE ARCHITECT OR HIS ENGINEER.
- 11. ALL WORK SHALL BE PERFORMED IN CONFORMANCE WITH THE LATEST COMMONWEALTH OF MASSACHUSETTS

BUILDING CODE AND THE STRUCTURAL STEEL INSTITUTE SPECIFICATIONS FOR BUILDINGS AND BRIDGES.









PROPSOES PARILAL ELEVATION AT SEAR

A OMMONWEALTH NEW FIRE ESCAPE BOSTON, MA 54





2020035 Scale: AS NOTED 6-16-2021 rawn 3 ir DF/AC

tvino Namo

PROPOSED FLOOR PLANS

